



FEED WAGON 340

Standard 340 Specifications

- * 550 x 20 Tires
- * Single Axle with Q873 Hubs
- * Total Machine Weight:
13,400 lbs

340 LH Options Additional Charge

- * RH Conveyor
- * 8" Solid Extensions
- 12" Extensions
- * Bunk Guard



FEED WAGON 480

Standard 480 Specifications

- * 1600 x 24 PLY Tires
- * Single Axle with Q881 Hubs
- * Total Machine Weight: 14,700 lbs

480 LH Options Additional Charge

- * RH Conveyor
- * 8" Solid Extensions
- 12" Extensions
- * Bunk Guard
- Tandem Axle With 385R22 .5 Tires



FEED WAGON 640

Standard 640 Specifications

- * 1600 x 20 24 PLY Tires
- * Single Axle with Q881 Hubs
- * Total Machine Weight: 18,000 lbs

640 LH Options Additional Charge

- * RH Conveyor
- * 8" Solid Extensions
- 12" Extensions
- * Bunk Guard
- * Tandem Axle With 395 x 20 Tires - Or 600/5022.5
Tires
- * PTO Up Charge with 1 3/4x20 Spline



MEYERINK FARM SERVICE, INC.
605-337-2621 * PLATTE, SD

36794 SD Hwy 44 • Platte, SD 57369

Phone: 605-337-2621

Fax: 605-337-2527

Email

davem@meyerinkfs.com or

duanem@meyerinkfs.com

www.meyerinkfs.com



MEYERINK FARM SERVICE, INC.
PLATTE, SD

**BUILT
TO
LAST**

Feed Wagons Built to Last

Heavy duty materials and quality precision manufacturing for better long term solution for your operation.

Standard Equipment Included:

- 1000 RPM constant velocity with PTO shaft with 1 3/8" x 21" spline
- 4' 8" chain conveyor-hydraulic flipper with magnets
- 640 XL scale with compression load cells
- (2) hydraulic outlets
- Stainless steel bottom liner
- Folding ladder
- Rear light
- Rear oil bath
- 7000lb jack
- Fenders

Scale Options

- 640 XL 640M with 4" display
- 640M with 2CT 4" display cable
- Point Bluetooth



Right Hand Side Option

- Available in right hand discharge
- 1,000 RPM CV PTO 1 3/4 x 20 Spine
- (3) Hydraulic outlets

Truck Mountable

- Most 340-480 models can be mounted and configured to a wide variety of trucks to fit your application needs.

